

SMD Power Inductors For Automotive
Size 4018B

- Magne c shield type wound inductor for power circuits using a ferrite magne c material
- High magne c shield construc on and compa ble with high-density moun ng.
- Larger current and lower Rdc were achieved by op mizing the ferrite core figure.
- Opera ng temperature: –55 to +125°C(including self-tem perature rise)
- AEC-Q200 qualified
- Quan ty: 3000pcs
-


Dimensions: [mm]





Land Pattern: [mm]





Typical Electrical Characteristics:























Soldering Reflow:

Preheat condition: 150 ~200℃/ 60~120 sec.


Allowed time above 217℃: 60~90 sec.

Max temperature: 260℃.

Allowed Reflow time: 2x max.


Packaging Information:

Tape Dimension:




Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
NRSA4018B	4.3±0.1	4.3±0.1	1.5±0.1	4.0±0.1	8.0±0.1	12.0±0.3	2.25±0.1	1.75±0.1	0.30±0.05

Peel force of top cover tape:




The peel force of top cover tape shall be between 0.3 to 1.17 N

Reel Dimension：[mm]



Packaging Quantity:



3000 Pcs/Reel　　3 Reel /Inner box(9K Pcs)　　3 Inner box/Carton box(27K Pcs)

Cautions and Warnings:

Storage Conditions：

Operation Instructions: